


Dual Row Jumpers (TYPE JU)

Series	# of Contacts	Connection Type End 1 and 2	Termination Type	Wire Length	_	ell Material and Finish	Options
JUM Jumper	09 15 21 25 31 37 51 65	MNSO Female (Socket Connector) MNPO Male (Pin Connector)	WD Pre-Wired PTFE WC Cable	XX.X Length in Inches		N Aluminum Shell, Electroless Nickel Plated CD Aluminum Shell, Cadmium Plated B Aluminum Shell,	ETH End Threaded Hole,#0-80 EJS End Jackscrew (Pin Only) HTE High Temp. Epoxy C Color Coded
	WWW YYWW					S Stainless Steel Shell, Passivated T Titanium Shell Unplated	RH RoHS COMPLIANT
			MANAGAT				







	PIN				[0.64] SOCKET							
	•	English (IN)			ı			Metric	(mm)			'
ı		CONTACTS	"A"	"B"	"C"	"D"		"A"	"B"	"C"	"D"	
		9	0.375	0.270	0.160	0.163		9.53	6.86	4.06	4.14	
		15	0.450	0.345	0.235	0.238		11.43	8.76	5.97	6.05	
		21	0.525	0.420	0.310	0.313		13.34	10.67	7.87	7.95	
		25	0.575	0.470	0.360	0.363		14.61	11.94	9.14	9.22	
		31	0.650	0.545	0.435	0.438		16.51	13.84	11.05	11.13	
		37	0.725	0.620	0.510	0.513		18.42	15.75	12.95	13.03	
		51	0.900	0.795	0.685	0.688		22.86	20.19	17.40	17.48	
		65	1.075	0.970	0.860	0.863		27.31	24.64	21.84	21.92	
2013 0	mnetics Conn	ector Corporation										CAGE Code 6187

© 2013 Omnetics Connector Corporation