






Micro-D

Standard Micro-D

■ Metal Shell Micro-D Discrete Leadwire (TYPE WD)

Series	# of Contacts	Shell Material and Finish	Hardware	Termination Type	Options
MMD Male (P - Pin) 	009	N (STD) Aluminum Shell, Electroless Nickel Plated	00 - NONE, Ø	WD - Discrete Leadwire  WIRE AWG: 6 - 26 AWG (STD) 8 - 28 AWG 0 - 30 AWG WIRE TYPE: Q - NEMA HP3 (FORMERLY M16878/4 &/6) (STD) R - M22759/11 S - M22759/33 WIRE LENGTH: 18.0 - 18.00" (STD) XX.X - CUSTOM LENGTH COLOR SCHEME: 1 - 10 REPEATING (STD) 2 - BLUE 3 - WHITE 5 - YELLOW	HTE High Temp. Epoxy  RH RoHS COMPLIANT 
	015		C Aluminum Shell, Cadmium Plated		
	021	02 - JACKSCREWS, STD LENGTH, HEX HEAD (STD)			
	031	03 - JACKSCREWS, STD LENGTH, SLOTTED			
	037	B Aluminum Shell, Black Anodized	04 - JACKSCREWS, LONG, HEX		
051*	05 - JACKSCREWS, LONG, SLOTTED				
Female (S- Socket) 	*(Use 512 for Two Row 051 and 513 for Three Row 051)	P Stainless Steel Shell, Passivated	06 - 07 FLOAT- MOUNT OPTIONS		

Example



MMDP-025-N00-WD6Q18.0-1-HTE

■ Standard

"n"	Rows	FEMALE	MALE
9	2	A99100-009	A98100-009
15	2	A99100-015	A98100-015
21	2	A99100-021	A98100-021
25	2	A99100-025	A98100-025
31	2	A99100-031	A98100-031
37	2	A99100-037	A98100-037
512	2	A99100-512	A98100-512
513	3	A99100-513	A98100-513