






# Micro-D

## Standard Micro-D

### ■ Metal Shell Micro-D Solder Cup (TYPE SS)

Series	# of Contacts	Shell Material and Finish	Hardware	Termination Type	Options
<b>MMD</b> Male (P - Pin) 	<b>009</b>	<b>N (STD)</b> Aluminum Shell, Electroless Nickel Plated	<b>00</b> - NONE, Ø	<b>SS</b> Solder Cup 	<b>HTE</b> High Temp. Epoxy 
	<b>015</b>		<b>01</b> - FIXED		
	<b>021</b>	<b>C</b> Aluminum Shell, Cadmium Plated	<b>02</b> - JACKSCREWS, STD LENGTH, HEX (STD)		
	<b>025</b>		<b>03</b> - JACKSCREWS, STD LENGTH, SLOTTED		
	<b>031</b>		<b>04</b> - JACKSCREWS, LONG, HEX		
	<b>037</b>		<b>05</b> - JACKSCREWS, LONG, SLOTTED		
<b>051*</b>	<b>B</b> Aluminum Shell, Black Anodized	<b>06</b> - FLOAT MOUNT, FRONT MOUNTED			
Female (S- Socket) 	*(Use 512 for Two Row 051 and 513 for Three Row 051)	<b>P</b> Stainless Steel Shell, Passivated	<b>07</b> - FLOAT MOUNT, REAR MOUNTED	<b>RH</b> RoHS COMPLIANT 	

### Example



MMDS-025-N00-SS-RH

### ■ Standard

"n"	Rows	FEMALE	MALE
9	2	A99000-009	A98000-009
15	2	A99000-015	A98000-015
21	2	A99000-021	A98000-021
25	2	A99000-025	A98000-025
31	2	A99000-031	A98000-031
37	2	A99000-037	A98000-037
512	2	A99000-512	A98000-512
513	3	A99000-513	A98000-513